

MANUAL TILTING ELECTRIC BRATT PAN - BOTTOM IN DUPLEX 2304 - 50 L



- External paneling in stainless steel
- Work surface in AISI 304, 2 mm thick
- Height-adjustable work surface from 855 to 900 mm
- Tilting bratt pan with cooking tank and manual tilting
- Stainless steel tank with rounded corners for thorough cleaning
- Bottom in DUPLEX 2304, 10 mm thick
- Tank water filling via valve and spout
- Double skinned lid with rear drainer to transfer condensate into the tank
- Hinges in AISI 304 satin steel with counter-balance lid and front handle for lifting
- Heating with Incoloy heating elements positioned under the tank
- Temperature regulation via thermostat between 50°C and 300°C
- Equipped with safety thermostat
- Cooktop 726 x 400 mm, capacity 50 L
- Heating interruption via micro-switch if the tank is lifted
- Indicator lights to monitor the correct operation of the appliance
- Height-adjustable stainless steel feet

TECHNICAL SPECIFICATIONS

Dimensions (mm)	800x700x900
Volume (m ³)	0,90
Weight (kg)	160

ELECTRICAL CONNECTION

kW	10
Power supply	VAC 400/3N 50/60Hz
Cold water inlet	1/2"

